

8CH Full Real Time Network video recorder

Product Model : FS-RF6-01008M-8P



FEATURES

- ◆8CH full real-time network video access, 1U NVR case
- ◆H.264 dual-stream decoding, embedded Linux operation system ◆
- Support sync video recording, remote monitoring, backup
- ◆SupportVGA/HDMI sync output , support 2160P HD preview
- ◆Support amplification preview and playback video image
- ◆Standard ONVIF, RTSP, GB28181 protocol
- ◆Support external alarm, bidirection talk,alarm snapshot,email sending functions
- ◆Support 4 standard POE power supply
- ◆Support DDNS, EMAIL, UPNP, NTP, P2P,etc
- ◆Support WEB, mobile viewer, Client, CMS monitoring
- ◆ support IPC intelligent functions (target counting, items left/lost, electronic fence, crossing detection, retrograde detection, departure detection)
- ◆Support grouping disk quota, and disk inventory two storage pattern, distribute different video storage capacity or cycle according to different channels
- ◆ Support IPC centralized management, including IPC parameters configuration, import and export information , information real time acquisition , etc
- ◆Support channel grouping, preview round touring
- ◆ Support network detection (network flow monitoring, network wireshark, network clear) function,etc
- ◆Support max 8CH sub stream sync playback and multi-channel sync play backward
- ◆Support instant playback
- ◆The new UI interface, support a key to open the video recording
- ◆Support dual password authentication、 IP filter,

Product parameters

VIDEO	
Network video input	8CH
Network access bandwidth	40Mbps
Video compression	H.264
Video output	1 CH VGA output (1920×1080@60HZ,1280×1024@60HZ)
	1 CH HDMI output(1920×1080@60HZ,1280×1024@60HZ)

Display mode	Synchronous output
System mode	8 digits +9 preview +4 playback
Video bit rate	16-8000Kbps
Video resolution	5MP/4MP/3MP/1080P/960P/720P/D1/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Image display	1/4/6/8/9 image display
Snapshot mode	Support timing snapshot, manual snapshot, JPEG format
Motion detection	Support 396(22*18) surveyed area can be set in every screen and multi-level sensitivity adjustable
Privacy mask	Support 4 zones
intelligent detection	support IPC intelligent functions (target counting, items left/lost, electronic fence, crossing detection, retrograde detection, departure detection)
AUDIO	
Audio compression	G.711u
Audio input	1 CH RCA port (IPC complex audio input)
Audio output	/
Bidirectional talk input	/
VIDEO RECORDING AND PLAYBACK	
Video frame rate	1-30fps
Record mode	manual/Timing record and alarm record/Timing record/alarm record/Stop record
Playback ability	Support 4CH sub stream sync playback
Playback mode	Instant playback, local record, Playback snapshot, external file playback
Record search	Time, calendar, channel search, event search, (ANR, regular video, motion detection video, alarm video, intelligent detection video)
Video playback	Start time, play/pause, stop, forward, backward, single frame,forward 30 seconds, backward 30 seconds,fast play(1-256X), slow play(1-1/32X)、 1/4 split screen, previous page, next page, backup, capture, show hidden progress bar, full screen,roller amplification time bar precise playback
STORAGE AND BACKUP	
Storage interface	1*SATA
HDD capacity	Single max.8TB
Disk grouping	Accordinging video channels to set HDD quantity
Disk quota	Accordinging video channels to set HDD storage capacity
Backup location	Local, network
Array type	/
Hot-backup management	/
Backup method	USB mobile hard disk, U disk, network backup
ANR	Support FSAN IPC (with TF card) ANR
Network protocol	TCP/IP,HTTP,HTTPS,DDNS,SMTP(SSL),DHCP,PPPoE,UPnP,NTP,P2P
Interface protocol	ONVIF、 RTSP、
Protocol port	ONVIF/RTSP/HTTP/HTTPS/RTMP port customized

Mobile surveillance	Support Apple, Android
Internet explorer	Support IE, Chrome, Firefox, Safari
Display function	Channel shortcuts: modify the channel, 3D positioning, display AI intelligent rules and results, capture, voice intercom, channel audio, manual recording, instant playback, video parameters
	Desktop display: audio input, volume, alarm information (deployment/removal), P2P cloud service, network information, Output adjustment, system information, device list (showing whether IPC is online or not, recording type), organizational structure (custom channel classification for quick preview), channel round tour, 1/4/6/8/9 split screen, open round tour, open linkage preview, file backup、 full screen、 hide OSD、 PTZ control,
IPC timing	Manual/auto/timing/reconnect timing to IPC timing
Alarm linkage	Send email, audible warning (buzzer), alarm on monitor, upload to center, record, snapshot, preview, PTZ linkage
Network detection	Flow monitoring, network wireshark, network test
User management	User add, delete, modify, permission management,FACEeye Scan the QR code to retrieve the password
	Auxiliary users(secondary password protection)
Manage IPC	Modify IPC parameters
Network protocol	TCP/IP,HTTP,HTTPS,DDNS,SMTP(SSL),DHCP,PPPoE,UPnP,NTP,P2P
EXT INTERFACE	
Network interface	1*RJ45 100M adaptive Ethernet port
POE interface	4CH (IEEE 802.3af) Max. power output≤40W
Alarm input	2CH
Alarm output	1CH
RS-485	1CH
USB Port	Front panel: 1*USB2.0 , Rear panel: 1*USB2.0
GENERAL	
Power supply	DC48V/3A (Power plug specification optional)
Power consumption	<10W (Without HDD)
temperature/humidity	-10°C ~ 55°C/10 % -90 %
Dimension(mm)	300(L)x209(W)x48.5(H)mm
Weight/PCS(g) (without HDD)	2kg (Without HDD)

Product size and interface



- 1. Alarm input
- 2. Alarm output
- 3. RS485
- 4. VGA video output
- 5. HDMI video output
- 6. USB 2.0
- 7. RJ45 network port
- 8. PoE power supply port
- 9. DC48V power port
- 10. Power switch